



No. 07 Jack Daniel's car, driven by Casey Mears



Jeff Burton drives the Caterpillar Chevy for Richard Childress Racing

INTAKE MANIFOLD BOLT KITS



Not only will these premium quality ARP fasteners help prevent intake manifold leaks, but **one is drilled to allow for a safety wire**. What's more, they're rated at **170,000 psi** and feature precision rolled threads for optimum engagement, to prevent galling and promote more consistent torque loading. Wide under-head flange design and companion flat washers provide even load distribution and facilitates optimum sealing of gasket surfaces. Made of corrosion resistant stainless steel. Washers included and bolt drilled for NASCAR inspector's wire lock.

Application	Part No.
CHEVROLET	
SB 2, drilled	334-2104
SB 2, tall deck	334-2105
Small block, 1.000", drilled	334-2102
Small block, 1.250", drilled	334-2103
V6 Chevy 90°, 1.000", drilled	333-2101
FORD	
SVO 351 cid, Jack Roush design, drilled	354-2102

DRILLED HEADER BOLTS

ARP offers special NASCAR header bolts that have been drilled for use of safety wire. They are made from heat-treated 8740 chrome moly steel (with a black oxide finish - rated at **180,000 psi**) or Stainless 300 that is polished to a bright shine (nominally rated at **170,000 psi** tensile strength – considerably stronger than Grade 8 hardware), and engineered to provide complete reliability in the most severe racing environments. They are available in hex or 12-point heads. Through use of safety wire, exhaust headers will maintain original tightness and can't back off!



Application	Qty	Dia.	UHL	Wrenching	Black Oxide		Stainless 300	
					Hex	12-Point	Hex	12-Point
CHEVROLET								
Chevy small block, drilled	12	3/8	.750	3/8	100-1103	100-1203	400-1103	400-1203
Chevy big block, drilled	16	3/8	.875	3/8			400-1104	400-1204
UNIVERSAL								
Universal, drilled	16	3/8	.750	3/8			400-1105	400-1205
Universal, drilled	12	3/8	.875	3/8			400-1106	400-1206

BRAKE HAT BOLT KITS



The perfect upgrade for many original brake hat bolts, this ARP kit features bolts produced from only the finest quality 8740 chrome moly. Features an exclusive 12-point cap screw design and appropriate grip length for the application. All brake hat bolts are drilled for safety wire lock. Rated **200,000 psi** tensile strength.

Application	UHL	Part No.
5/16-24, 32 pieces	.880	300-0801
5/16-18, 32 pieces	.850	300-0802
1/4-28, 48 pieces	.750	300-0803

JACK DANIEL'S OLD NO. 7 BRAND, the stylized no. 07 and PACE YOURSELF, DRINK RESPONSIBLY are all trademarks of Jack Daniel's Properties, Inc. The RCR checkered flag logo is a registered trademark of RCR Enterprises, LLC. CLINT BOWYER and Clint Bowyer's autograph are trademarks of Clint Bowyer, Inc. All trademarks, personal likenesses and the likeness of the no. 07 race car are used under license from their owners. The stylized no. 31 and the RCR checkered flag logo are registered trademarks of RCR Enterprises, LLC. JEFF BURTON and Jeff Burton's autograph are trademarks of Jeff Burton Autosports, Inc. CAT, CATERPILLAR, CAT RACING, their respective logos, "Caterpillar Yellow," the POWER EDGE trade dress, other marks and corporate identity used herein are trademarks of Caterpillar and may not be used without permission. All trademarks, personal likenesses and the likeness of the no. 31 race car are used under license from their owners.