

Head Studs

5.9L 12V Cummins (1989-98) ARP2000	247-4203
5.9L 12V Cummins (1989-98) Custom Age 625+	247-4205
5.9L & 6.7L 24V Cummins (1998 & later) ARP2000	247-4202
5.9L & 6.7L 24V Cummins (1998 & later) Custom Age 625+	247-4204
3.9L 4BT Cummins ARP2000	247-4206
3.9L 4BT Cummins Custom Age 625+	247-4207
C8.3 ARP2000	247-4209
ISL 12V ARP2000	247-4210
ISL 24V ARP2000	247-4211
ISV5.0 ARP2000	247-4302

Main Studs

3.9L 4BT Cummins, 2 bolt	247-5404
5.9L 12V Cummins	247-5402
5.9L 24V Cummins, late '97-'06, 2-bolt	247-5401
5.9L & 6.7L 24V Cummins (2004 & later) with factory block stiffener place, 0.600" counter bore	247-5403
6.7L Dodge/Cummins (2007 & later) with factory block stiffener plate, 2 bolt	247-5405
ISL ARP2000	247-7201
ISF2.8 ARP2000	247-5407
AISV5.0 ARP2000	247-5801

Rod Bolts

5.9L 12V/24V Cummins (Angled cap rod) ARP2000	247-6303
3.9L 4BT Cummins (Angled cap rod) ARP2000	247-6304



Flywheel Bolts

	UHL	Thread	
5.9L 12V/24V Cummins (2004 & earlier)	1.250	M12 x 1.25	147-2802

Flexplate Bolts

	UHL	Thread	
5.9L 12V & 24V Cummins	0.700	M12 x 1.25	147-2901



Harmonic Damper Bolts

	UHL	
5.9L 12V/24V Cummins (2007 & earlier)	1.425	147-2502
5.9L & 6.7L 24V Cummins (2008 & later)	1.725	147-2503

Ring Compressors

3.740"	899-7400	4.080"	900-0800
3.750"	899-7500	4.090"	900-0900
3.760"	899-7600	4.130"	900-1300
4.060"	900-0600	4.140"	900-1400
4.070"	900-0700	4.155"	900-1550
4.075"	900-0750	4.212"	900-2125



Rocker Pedestal Studs

24V Cummins	247-7201
-------------	----------